



Notes—
All fillets to be 5/8 rad & all rounded corners 1/2 rad unless otherwise specified.
Wall thickness to be not less than indicated.
Finish where shown.
Each bolster shall bear the casting No., date of manufacture, and manufacturer's name or trade mark, legibly & durably stamped on pads provided for the purpose, or cast on.
A serial No shall be legibly & durably stamped in characters 1/2" high on each bolster on a pad provided for the purpose

CASTING WEIGHT

2170 - 2213

DEW156

COPYRIGHT © RESERVED
THE DESIGN AS DETAILED ON THIS DRAWING IS THE PROPERTY OF CLYDE ENGINEERING (AUSTRALIA) PTY. LIMITED AND/OR ITS ASSOCIATES AND MUST BE RETURNED ON DEMAND. IT IS SPECIFICALLY ON THE STRICT CONDITION THAT EXCEPT WITH OUR WRITTEN PERMISSION IT MUST NOT BE REPRODUCED, COPIED OR COMMUNICATED TO ANY THIRD PARTY NOR BE USED FOR ANY PURPOSES OTHER THAN THAT STATED IN THE PARTICULAR ENQUIRY, ORDER OR CONTRACT WITH WHICH IT IS ISSUED. THE RESERVATION OF COPYRIGHT IN THIS DOCUMENT EXTENDS FROM EACH DATE APPEARING THEREON AND IN RESPECT OF THE SUBJECT MATTER AS IT APPEARED AT THE RELEVANT DATE.

NOTE: APART FROM DELETION SHOCK ABSORBER BRACKETS, THIS ITEM IDENTICAL TO P/N 2410805

REV. DATE		REVISION		BY		CHK.		DATE		REVISION		BY		CHK.		DATE		SCALE	
A 20.4.81		INITIAL ISSUE		DGB				29.4.81								1:4		1:2	
FIRST USED ON G.R. G226C-2 LOCOMOTIVES: 2170-2180										APPROVED									

MATERIAL: CAST STEEL
SYMBOL: AS 2074/C4-1
DRAWN: DGB

THE CLYDE ENGINEERING COMPANY PTY. LIMITED
A MEMBER OF THE CLYDE INDUSTRIES GROUP OF COMPANIES
CLYDE, N.S.W., AUSTRALIA
INCORPORATED IN QUEENSLAND
BOLSTER

2411426
(2410805)